Annex I: Technical Specification and Bill of Quantities for the supply and installation full function brequette
- 1 · 1 · 1 · 1

	Production plant in					
Item No.	Description	Unit	Quantity	Remark		
1b	Option B (Brequette making integrated with Conveyer for Mixing)	Set	1			
	Main Part include Brequetting Machine, Conveyor and Control Cabinet					
	Capacity 300-350Kg/Hr					
	V-belt/gear power transmission system					
	Power of main engine=30KW maximum					
	Estimated life span: minimum of 10 years					
	including service and operational tools					
	Minimum of 2 year warranty					
	Complete installation, service and operation manual in English language			·		
	CE ISO certified					
3	Hammermill charcoal Crusher with Cyclone	pcs	1			
	Capacity: 500-700kg/hr					
	Dust free during operation technology: a) With ventilated cyclone to absorb dust b) Completely sealed with gaskets c) Indirect Inlet and outlet (e.g. around a corner)					
	Safe technology: no risk of dust explosion					
	Maximum of 2700rps					
	Screen mesh size: maximimum: 5mm					
	All flanges/edges/ joints sealed with gaskets = dustproof.					
	Non-corrosive, durable structure, very high quality workmanship					
	including service and operational tools	-				
	Complete installation, service and operation manual in English language Simple and safe operation and installation					
	Reduced noise (less than 80 db)					
	V-belt drive system 3 Phase, 380V, 50HZ, max KW 18.5KW					
	Estimated life span: minimum 10 years	-				
-	Minimum of 2 year warranty	-				
	CE ISO certified	+	 			
4	Carbonizer/Kiln for Briquette charcoal production	pcs	3			
H	Capacity: 1000 Kg per kilning	pcs	,			
\vdash	Internal cone: 2mm thick and perforated hole 4mm carbon steel					
	Outer body: 2mm thick carbon steel					
	Outer cone and external body cover: 1.5mm thick carbon steel					
	Safe technology: clean carbonizer/reduced air pollution					
	Non-corrosive, durable structure, very high quality workmanship					
	Complete installation and operation manual in English language	1				
	Simple and safe operation and installation					
	Minimum of 1 year warranty					