



United Nations Children's Fund  
UNICEF- Ethiopia  
P.O. Box 1169  
Africa Hall  
ADDIS ABABA  
Ethiopia

Telephone  
Facsimile  
Email  
<http://www.unicef.org/ethiopia>

---

**INVITATION TO BID**

**LITB-2021-9170779**

**15 October 2021**

**UNITED NATIONS CHILDREN'S FUND (UNICEF)**

**Wishes to purchase**

**WAREHOUSE ITEMS**

**Due Date: 10 November, 2021 at 2:00PM**



---

THIS INVITATION TO BID HAS BEEN:

---

**BID FORM**

BID FORM must be completed, signed and returned to UNICEF.  
Bid must be made in accordance with the instructions contained in this INVITATION.

**TERMS AND CONDITIONS OF CONTRACT**

Any Purchase Order resulting from this INVITATION shall contain UNICEF General Terms and Conditions and any other Specific Terms and Conditions detailed in this INVITATION.

**INFORMATION**

Any request for information regarding this INVITATION must be forwarded by email to the attention of the person who prepared this document, with specific reference to the Invitation number.

The Undersigned, having read the Terms and Conditions of INVITATION No. **LITB-2021-9170779** set out in the attached document, hereby offers to execute the services specified in the Terms and Conditions set out in the document.

Signature: \_\_\_\_\_

Date: \_\_\_\_\_

Name & Title: \_\_\_\_\_

Company: \_\_\_\_\_

Postal Address: \_\_\_\_\_

Tel No: \_\_\_\_\_

Fax No: \_\_\_\_\_

E-mail Address: \_\_\_\_\_

Validity of Offer: \_\_\_\_\_

Currency of Offer: \_\_\_\_\_

Please indicate after having read UNICEF Price & Discount stated in the Specific Terms and Conditions, which of the following Payment Terms are offered by you:

10 Days 3.0% \_\_\_\_\_ 15 Days 2.5% \_\_\_\_\_ 20 Days 2.0% \_\_\_\_\_ 30 Days Net \_\_\_\_\_

Other Trade Discounts \_\_\_\_\_

Item No	Item Description	Quantity/Unit	Unit Price	Amount
<b>SCHEDULE NO: 1 PSS</b>				
00010	U490000	12 each		
	<p>GP40-GP55N models are equipped with a GCT GK45 LPG engine with standard catalytic converter that delivers good performance, excellent fuel economy Picture attached</p>			
00020	U674330	8186 each		
	<p>Rack Heavy Duty Storage Racking System Pallet size will be 1200mm deep 1000mm wide and 1400mm high including pallet Pallet weight = 1000Kgs Height of the rack #please refer to figure 1,2 &amp;3 below Horizontal beam length- 2300mm however vendor can propose other that will optimize storage space Depth of rack -1200mm Number of level-three (Ground) and five (for the upper) Bay load -2000 kgs. (based on two pallets per level) Based on the proposed configuration vendor should quantify the following Upright (vertical)frame base plate with required quantity of anchor bolts Horizontal bracing Diagonal bracing Horizontal beam with required number of locking pin Material: Material should be of high grade steel /as per EPSA sample rack Treatment: All the components shall be thoroughly pre-treated, Painting: all the components shall be painted with epoxy powder coating and film thickness of minimum 50 microns or better. Colour: Orange colour for beam and base plate rest all components should be in blue colour. Quantity required = 8186 pallet space + 20% = racks for 10,000 pallet spaces</p>			
00030	U674330	60 each		
	<p>Picking and Packing trolley An all steel, corrosion resistant three tier robust trolley suitable for warehouse as well as the workshop. The trolley as two fixed wheels and two swivel casters fitted with solid rubber tyred wheels. The steel base and shelf have a non-slip surface (base and shelves will be coated with structure type epoxy coating) and an all-round protection buffer. Two handles are fitted for convenience. Spec for the three tier trolleys Dimensions H x W x L mm: 1100 x 610 x 1260 Overall dimensions incl. handles: H x W x L: 1275 x 610 x 1260mm Shelves width and length mm: 610 x 1260 Bottom shelves gap need to be mm: 350-450 Capacity kg: 200 Caster Wheels mm: 150mm diameter</p>			



Item No	Item Description	Quantity/Unit	Unit Price	Amount
00040	U674330	20 each		
	<p>Rider Floor Cleaning Machine</p> <p>Type: Rider automatic floor scrubber            Cleaning capacity:2500m2/h            Cleaning feature: Clean different surfaces (Concrete floors, tiled floors, vinyl, sealed wood, marble, and othesurfaces) with one machine and spend minimal time changing out accessories (Slide-out decks for edge cleaning and easy-to-swap brush and cylindrical decks)Built to tackle everything from small area floor cleaning, warehouse floor cleaning, store aisle (narrow passages) floor cleaning, and large area floor scrubbing.            Working Condition:            Water Usage: Reduced, designed to minimize water usage, providing a big productivity boost            Batteries: Maintenance free, with on board battery charger            Brush/Pad Diameter: 60cms            Brush types: Equipped with different types of brushes (multiple types of brushes to suit different types of flooring and applications) with easy brush changing arrangement.            Central motor applies even brush pressure Corrosion-resistant materials for long life.            Robust and rigid construction to withstand rough handling Emergency stop button for an immediate machine stop Automatic speed reduction in bends            Automatic detachment of the vacuum rail in case of inadvertent impact protects against damage            Ergonomic hand grip with control and display            Fresh water tank with hose quick filling            Wheels: Polyurethane            Duty Cycle Heavy duty. Capable of cleaning continuously for more than 8 hours (suitable size water and solution storage)            Sound Level: With built-in sound attenuation, enables your operators to clean during business hours and without the fatigue and irritation            Simplicity:            Maintenance:            Warranty :2 Yrs. Parts, 2 Yrs.            Batteries: 24 V            Brush/Pad Pressure: 15 KG            Brush Speed: 150 rpm            Working width vaccume- 70-80 cm            Two tank system            Fresh water tank : 65 L            Grey water tank: 75 L            Motor out put: 1000 W            Automatic speed control            Automatic brush and water stop            Emergency Stop Button            Water fill level display and operating hours counter            Battery charge status Display</p>			
00050	U674330	10 each		

Item No	Item Description	Quantity/Unit	Unit Price	Amount
	<p>Pallet Mover (walkie stacker truck)</p> <p>To facilitate the movement of commodities from receiving, put away, stock control, order picking to dispatch.</p> <p>Power source: Battery</p> <p>Operator type: Pedestrian</p> <p>Load capacity:2000Kgs</p> <p>Tyres:High grade polyurethane</p> <p>Ground clearance forks lowered:100mm</p> <p>Turning radius1500mm</p> <p>Height with mast lowered2200mm</p> <p>Lift height5000mm</p> <p>Height, mast extended5500mm</p> <p>Operating hours8 hours</p> <p>Service brake Electric</p> <p>Type of drive control Stepless</p> <p>Battery Capacity48V/300AH</p> <p>Level of noise (at driver) 65dBA</p> <p>Documentation: Operation &amp; Maintenance Manuals (Maintenance manual shall include all Electrical &amp; Hydraulic Circuits with BOM) CD Media &amp;Hard copy</p> <p>Training: The supplier shall train Two Engineers of the reach trucks at supplier's works for a period of 5 working days.</p> <p>Warranty: Performance Guarantee for a minimum period of 24 months</p> <ul style="list-style-type: none"> <li>- High capacity retention at high lifts, up to 5 m, and excellent visibility through the mast, fork carriage and overhead guard, ensure top performance in any warehouse application.</li> <li>- Features with advanced mast handling # for fast lifting/lowering, smooth start/stop of reach movements and accurate tilt control.</li> <li>- Easy-use Pre-set height selector for allowing faster, safer stacking.</li> <li>- Features with intuitive joystick control. (Joystick hydraulic control)</li> <li>- Fork positioner with shift and tilt function centring</li> <li>- Battery changing device and quick battery locking system</li> <li>- Active Sway Control and alarm for driving, lifting and lowering</li> </ul>			

00060 U674330 7 each

Dock levelers

Technical Specification of Hydraulic Dock Levellers#

Dock Leveller System Description

Provide fixed-in-place adjustable loading and unloading platform for difference in height and gap between truck bed and warehouse loading dock.

Provide loading dock equipment, which has been manufactured, fabricated, and installed to withstand loads specified and to maintain performance criteria stated by manufacturer without defects or failure. Comply with ANSI MH14.1-1987 and ANSI 30.1-2007

The following description is for a hydraulic dock leveller to insure low maintenance and reliable performance:



Item No	Item Description	Quantity/Unit	Unit Price	Amount
	I. GENERAL: 1. Capacity: 6.5 ton 2. Platform Width: 2250mm 3. Platform Length: 2500mm 4. Platform Deck Thickness: 8mm high tensile steel safety for 10-ton tread plate for with abrasive non-skid finish 5. Lip Length: 500mm like the deck platform thickness or higher 6. Working Range above doc level: 600mm 7. Heavy Duty Control panel with Level controls & Fault and service indicators 8. Perimeter Weather Seal System / Brush Weather seal. Electrical power:3 phase 400 V, 50 Hz			

00070 U674330 20 each

Walkie End Riders Lift Truck

Power source: Battery  
 Operator type: Operator Standing  
 Load capacity:3000 kgs  
 Fork length and width: Suitable for ISO standard pallets with pallet entry rollers  
 Tyres: High Grade Polyurethane  
 Max lift height: 250 mm  
 Lowered forks height: 75-100 mm  
 Ground clearance (min): 25 mm  
 Turning radius: 1500 mm  
 Travel Speed (loaded): 10km/hr  
 Operating hours: 12 hours  
 Steering: Electric Power  
 Service brake: Electric

00080 U674330 7 each

Roller shutter doors(3m wide x 4.2m high)

- Panel shutter doors in ISO40 panelling
  - 3ph electrically operated insulated sectional door
  - 40mm insulated panels to come plastisol coated in a standard colour
  - 6 vision panels per door across one leaf
  - Door to include 3ph operation with direct drive motor and manual over-ride chain
  - Activation via Push button control in Deadman operation with self-closing and photo eye protection.
- Test and commission the door and leave site clean and tidy

**Incoterms & Delivery Requested**

**Lead Time & Related Charges**

Item No	Item Description	Quantity/Unit	Unit Price	Amount
<b>Packing</b>				
Unit :	Dimension.....x.....x.....cm	Weight.....kg	Volume.....cbm	
Total:	Dimension.....x.....x.....cm	Weight.....kg	Volume.....cbm	